



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3446 86" THREE TIER SCALLOP FOUNTAIN

3517 86" THREE TIER DOLPHIN FOUNTAIN

3524 77" THREE TIER SCALLOP FOUNTAIN

Open bag containing the pump kit **P460KP**. In the kit you will find:

1 - 40460 (460 gallon per hour pump)	1 - hose clamp
1 - 2" long piece of 3/4" clear tubing	1 - 12" long piece of putty tape
1 - 48" long piece of 1" clear tubing	1 - rubber stopper

1. Place pedestal on a firm surface where fountain will remain. Place the largest shell on the pedestal.
2. Find the pump, 3/4" clear tubing 2" long, 1" clear tubing 48" long, rubber stopper, hose clamp. Slip the piece of 3/4" clear tubing 2" long onto the outlet side of the pump. Then over top of the 3/4" clear tubing slip on the 1" clear tubing 48" long and attach with the hose clamp. Place pump in the pump house in the center of the shell and run the plug end of the electrical cord down the PVC pipe in the pump house and down through the pedestal. Retrieve cord from under pedestal and place in access hole in bottom of pedestal. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust the position of the rubber stopper on the power cord if necessary.
3. Position the largest shell on pedestal and level. To level shell, place level on the top rim of the pump house in the center of shell. Level in (2) Two directions left to right and front to back. Shim as needed.
4. Find the larger spacer that is 8" high. Run the 1" clear tubing 48" long through the center hole in spacer. Place spacer on top of pumphouse in center of shell and level as stated in step #3.
5. Find the second shell and run the 1" clear tubing 48" long up thru the PVC insert in the center housing of the shell. Position this shell on top of the large spacer and level. To level shell, place level on center housing in center of shell. Level as stated in step #3.
6. Find the smaller spacer that is 5.5" high. Run the 1" clear tubing 48" long through the center hole in spacer. Place spacer on top of center housing in center of shell and level as stated in step #3.
7. Find the third shell and run the 1" clear tubing 48" long up thru the PVC insert in the center housing of the shell. Position this shell on top of the smaller spacer and level. To level shell, place level on center housing in center of shell. Level as stated in step #3.
8. Before placing the finial on the fountain. Cut the 1" clear tubing 10" above the top surface of the center housing on the third shell. Find the piece of putty tape 12" long. Located in the center housing of the third shell you will see the PVC insert with the 1" clear tubing in the center. **Apply the putty tape around the 1" clear tubing and down into the PVC pipe, keeping the 1" clear tubing in the center of the PVC pipe.**
9. Find the finial. In the center of the finial you will see a PVC pipe. Insert the 1" clear tubing into the PVC pipe in the bottom of the finial and slide the finial down onto the center housing of the second shell. Position the finial on the fountain.
10. Find the drain plugs and insert snugly into the drain inserts located in the two shells of the fountain. Remove any tape and or dirt from the drain insert before you insert the drain plug.

STEP #11 IS FOR #3517 86" THREE TIER DOLPHIN FOUNTAIN ONLY

11. Position one 30" Dolphin in each of the four curved section of the pedestal.



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

12. Fill shells with tap water and plug pump into a 110VAC GFCI protected outlet. To adjust the water flow to the finial, unplug the pump and remove the finial from the fountain. Cut the 1" clear tubing another 1/2" shorter and reposition the finial on the fountain. If necessary repeat by cutting the 1" clear tubing another 1/2" shorter. This will regulate water flow from the finial until the desired result is achieved.

3446sup 12/28/06