



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3558 CLEOPATRA FALLS FOUNTAIN

Open the bag containing the pump kit **P16002**. In the kit you will find:

1 - 40160 (160 gallon pump)	1 - rubber stopper	1 - restrictor clamp
1 - 36" long piece of 1/2" clear tubing	1 - hose clamp	

1. Place the fountain base on a firm and level area where fountain will remain. To level the base, place a level on the top rim of the pumphouse located in the center of the fountain base. Level in (2) Two directions left to right and front to back.

Shim if needed.

2. Find the pump, the piece of 1/2" clear tubing 36" long, the hose clamp and the rubber stopper. Attach the piece of 1/2" clear tubing 36" long to the outlet side of pump with hose clamp. Place the pump in the pump house located in the center of the fountain base. Run the plug end of the power cord down the PVC pipe located in the pump house and down and out the bottom of the fountain base. Retrieve cord from under the fountain base. Place cord in the groove in bottom of fountain base. Slip the rubber stopper onto the power cord about 12" from the pump with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust the position of the rubber stopper on the power cord if necessary.

3. The **3558 CLEOPATRA FALLS FOUNTAIN** has 4 tiers of different sizes plus the finial. Stack the tiers one at a time starting with the largest to the smallest centered on top of the pumphouse. Level each tier by placing a level on the raised area in the center of each tier. Level in (2) Two directions left to right and front to back. **Shim if needed.** As you stack each tier on top of each other run the 1/2" clear tubing up through the center hole in each tier. Before you stack the finial onto the fountain. Trim the 1/2" clear tubing to the proper length. Find the restrictor clamp and slip it onto the 1/2" clear tubing with the open end of the restrictor clamp facing up. Close the restrictor clamp three clicks. Connect the 1/2" clear tubing to the copper pipe which is in the base of the finial. Adjust the position of the restrictor clamp so the finial will sit properly on the fountain.

4. Find the drain plug and insert snugly into the drain insert located in the fountain base.

5. Fill the fountain base with tap water and plug pump into a 110VAC GFCI protected outlet. Adjust water flow using the restrictor clamp until the desired result is achieved.

3558sup

12/1/06