

SET UP INSTRUCTIONS

3768 - 40" TREEFALL FOUNTAIN

1. Place the one piece waterfall on a firm and level surface where fountain will remain.
2. Open the bag containing the pump kit **P40013**. In the kit you will find:

1 - 40400 (400 gallon per hour pump)	1 - 1" x 3/4" reducing female adapter
1 - 3/4" kink free tubing 7" long	1 - 3/4" thread / barb adapter
1 - 2-hole rubber stopper	1 - LED light (36 white)
3. Find the 1" x 3/4" reducing female adapter and the 3/4" thread / barb adapter and screw the two pieces together. Find the 3/4" kink free tubing and attach one end to the barbed end on the 3/4" thread / barb adapter.
4. From the front of the fountain, at the bottom of the water fall, you will find a PVC pipe. Attach the slip end of the 1" x 3/4" reducing female adapter onto the end of this PVC pipe. Push the adapter onto the PVC pipe until it bottoms out
5. Find the pump, the LED light (36 white) and the 2-hole rubber stopper. Place the pump and the LED light into the water cavity located at the base of the waterfall. Run the power cords of the pump and the LED light out the hole located in the rear wall of the water cavity. Slip the rubber stopper onto the power cords about 12" from the pump and about 30" from the LED light. Insert the rubber stopper snugly into the hole.
6. Attach the piece of 3/4" kink free tubing onto the outlet side of the pump.
7. Find the drain plug and insert snugly into the drain insert located in the water cavity. Remove any tape and or dirt from the drain insert before you insert the drain plug.
8. Position the LED light inside the water cavity at the front wall.
9. Connect the power cord on the LED light to the transformer. Fill the fountain bowl with tap water. Plug the pump and the LED light transformer into a 110VAC GFCI protected outlet. If necessary, adjust the water flow using the dial type flow control located on the front of the pump

3768sup 5/16/13