



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3877 - 120" THREE TIER SAVONA FOUNTAIN

Open bag containing the pump kit **P70003**. In the kit you will find:

1- 02527 (700 gallon per hour pump)	1 – hose clamp	1 – tube of silicone
1 – 3/4" clear tubing 90" long	1 – #11 rubber stopper	1 – 4"X2" reducer bushing
1 – 1" clear tubing 6" long	1 – 2" PVC pipe 14" long	

1. Place the pedestal on a firm and level surface where the fountain will remain and level in all directions. Place the largest shell on the ground near the pedestal.

2 – Find the 2" PVC pipe 14" long and the 4" X 2" reducer bushing. Using PVC glue or silicone, insert the 4" X 2" reducer bushing into the 4" coupling located in the center of the large shell. Then insert the 2" PVC pipe 14" long into the 4" X 2" reducer bushing.

3. Find the pump, the #11 rubber stopper and the hose clamp. Place pump in the center of the largest shell and run the plug end of the power cord down the 2" PVC pipe located in the center of the large shell. Retrieve the power cord from under shell. Run the power cord down the hole that is through the pedestal. Retrieve the power cord from under pedestal and place in groove in bottom of pedestal. Place the largest shell on the pedestal. While placing the shell on the pedestal carefully pull the remainder of the power cord until all is hidden inside the fountain. Slip the rubber stopper onto the power cord about 18" away from the pump with the smaller end facing away from the pump. Find the tube of silicone and apply around the outside edge of the rubber stopper and around the power cord. Insert the rubber stopper snugly into the PVC pipe

4. Position the large shell on top of the pedestal and level in all directions.

5. Find the larger pump house and pump house plug and position it in the center of the large shell and level in all directions.

6. Find the larger spacer that is 26" high. Position this spacer on top of pump house and level in all directions. Find the 3/4" clear tubing 90" long. Insert one end of the 3/4" clear tubing into the water inlet hole that is in the pumphouse and feed up through the center hole in large spacer. The remainder of the 3/4" clear tubing will lay in the large bowl.

7. Find the second shell and feed the 3/4" clear tubing up thru the hole in the center housing of the shell. Position this shell on top of the spacer and level in all directions. Find the smaller pump house and pump house plug and position it in the center of the second shell and level in all directions.

8. Find the second spacer that is 20" high. Feed the 3/4" clear tubing up through the center hole in spacer. Position this spacer on top of pump house in center of shell and level in all directions.

9. Find the third shell and feed the 3/4" clear tubing up thru the hole in the center housing of the shell. Position this shell on top of the spacer and level in all directions.

10. Attach the opposite end of the 3/4" clear tubing onto the outlet side of the pump with the hose clamp. Move the pump into the pumphouse feeding the 3/4" clear tubing up through the fountain. Position the pump house plug in the opening in the pump house in the large and middle shells.

12. Find the finial and remove any excess concrete or tape from inside and both ends of the PVC pipe located in the center of the finial. Before placing the finial on the fountain. Cut the 3/4" clear tubing 10" above the top surface of the center housing on the third shell. **Find the piece of 1" clear tubing 6" long. Slip the 3/4" clear tubing all the way into the 1" clear tubing until both ends are even.** Insert the 1" clear tubing into the PVC pipe in the bottom of the finial and slide the finial down onto the center housing of the second shell. Position the finial on the fountain.

13. Find the drain plugs and insert them snugly into the drain insert located in the two larger shells. Remove any tape and or dirt from inside the drain insert before you insert the drain plug.



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

12. Fill each shell with tap water and plug pump into a 110VAC GFCI protected outlet. To adjust the water flow to the finial, unplug the pump and remove the finial from the fountain. Trim the 3/4" clear tubing another 1/2" shorter and reposition the finial on the fountain. If necessary, repeat by cutting the 3/4" clear tubing another 1/2" shorter. This will regulate water flow from the finial until the desired result is achieved.

3689sup **3/17/17**