



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3888 72" TWO TIER CORTONA FOUNTAIN W/ 14" PINEAPPLE

Open bag containing the pump kit **P29020**. In the kit you will find:

- 1 – KING 400 (400 gallon per hour pump)
- 1 - 42" long piece of 3/4" clear tubing

1 - rubber stopper

1. Place the pedestal on a firm and level surface where fountain will remain. To level pedestal, place level on the top rim of the pedestal. Level in (2) Two directions left to right and front to back. Shim as needed. Place the largest shell on the ground near the pedestal.
2. Find the pump and the rubber stopper. Place the pump in the pumphouse located in the center of the shell and run the plug end of the electrical cord down the PVC pipe. Retrieve the power cord from under shell. Run the power cord down the hole that is through the pedestal. Retrieve cord from under pedestal and place in groove in the bottom of the pedestal.
Place the largest shell on the pedestal. While placing the shell on the pedestal carefully pull the remainder of the power cord until all is hidden inside the fountain. Slip the rubber stopper onto the power cord about 15" from the pump. Insert the rubber stopper snugly into the PVC pipe.
3. Position the large shell on top of the pedestal and level. To level shell, place the level on the pumphouse located in the center of the shell. Level in (2) Two directions left to right and front to back. Shim as needed.
4. Find the second shell and place this shell centered on top of the pumphouse located in center of largest shell. Find the piece of 3/4" clear tubing 42" long. Insert one end into the hole located in the center of the second shell and down into the pumphouse. Reach inside the water inlet hole located in the wall of the pumphouse and attach the piece of 3/4" clear tubing onto the outlet side of the pump. Position the shell on the pumphouse and level. To level shell, place the level on the top surface of the center housing located in the center of the shell. Level as stated in step #3.
6. Before you trim the 3/4" clear tubing to length. Push the 3/4" clear tubing back down until the pump is resting on the bottom on the pumphouse. Cut the length of the 3/4" clear tubing to 12 1/2" above the top surface of the center housing of the second shell.
7. Find the finial. Slip the finial onto the 3/4" clear tubing located in the center of the second shell. Position the finial on the fountain.
8. Find the drain plugs and insert them snugly into the drain inserts located in the two shells. Remove any tape and or dirt from the drain insert before you insert the drain plug. Fill shells with tap water and plug pump into a 110VAC GFCI protected outlet. Adjust the water flow to the finial using the built in dial type flow control located on the front of the pump.

3888sup

6/17/11