



MASSARELLI'S®
MAKERS OF FINE STONE GARDEN ACCENTS

3529 - 36" Anaconda Wall Fountain



Fountain Information

- Two people are recommended for the installation of this fountain.

Fountain Components

- 3529B - One Piece Fountain
- 3529PL - Fountain Plug

Pump Kit P16024 Includes

- 40160 - 160 GPH Pump
- 9961 - 1/2" Clear Tubing - 6" Long Piece
- 9926 - 36LED White Light
- 1" x 3/4" Reducer Bushing
- 3/4" Thread / 1/2" Barb Adaptor
- 9945 - 2 Hole Rubber Stopper
- Hose Clamp
- Silicone

Tools Required

- Bubble Level
- Marker or Pen
- Tubing Cutter or Scissors
- Shims (only if leveling is required)

Set Up Instructions

1. Find the one piece base & wall piece and place it on a firm and level area where the fountain will be installed.
2. Locate the PVC insert inside the water basin on the left hand side. Find the pump and the LED light. Run the plug end of the pump and LED light power cords through the PVC insert. Retrieve the cords from the back of the fountain. Leave about 12" of slack on both power cords inside the water basin.
3. Find the 2 hole rubber stopper and silicone. Fill both holes of the rubber stopper with silicone and slip the rubber stopper onto the power cords by spreading the slits open. The rubber stopper should be about 12" from the pump and LED light. The smaller end of the rubber stopper should be facing away from the pump and LED light.
4. Apply silicone around the inside edge of the PVC insert and around the edge of the rubber stopper.
5. Retrieve both of the power cords from underneath the fountain and place both of the cords in the groove that runs out from the back of the fountain. Insert the rubber stopper snugly into the PVC insert. Apply more silicone around the rubber stopper and power cords to ensure a water tight seal.
6. Find the 1"x3/4" reducer bushing and the 3/4" thread / 1/2" barb adapter and screw the two pieces together. Find the 1/2" clear tubing and attach one end to the barbed end of the 3/4" thread / 1/2" barbed adapter. Attach the opposite end of the 1/2" clear tubing onto the outlet side of the pump. Use the hose clamp to secure the 1/2" clear tubing to the outlet side of the pump.
7. Stand in front of the fountain and locate the PVC pipe that is centered in the water basin. Insert the 1" end of the 1" x 3/4" reducer bushing onto the end of the PVC pipe. Push the 1" x 3/4" reducer bushing into the PVC pipe until flush.
8. Position the LED light on the floor of the water basin.
9. Find the Fountain Plug and place it on the four rests that are located in each corner of the water basin.
10. Fill the fountain with about 6" of water.
11. Connect the power cord on the LED light to the transformer. Plug in the power cord of the pump and LED light to your GFCI outlet. The fountain will start running.
12. You may need to adjust the water flow. To do so use the flow control dial located on the front of the pump.