



3882 - Chelsea Round Tiered Fountain



Fountain Information

- · This fountain holds approximately 2 gallons of water.
- Two people are recommended for the installation of this fountain.

Fountain Components

- 9737P- Pedestal
- 3363S Shell
- 4694 Finial

Pump Kit P16026 Includes

- 40160 160 GPH Pump
- 9917 White LED Light
- 9958 12" Piece of 1/2" Kink Free Tubing
- 9945 2 Hole Rubber Stopper

Tools Required

- Bubble Level
- Marker or Pen
- · Tubing Cutter or Scissors
- · Shims (only if leveling is required)

Set Up Instructions

- 1. Place the pedestal on a firm and level area where the fountain will be installed.
- 2. Find the shell and place beside the pedestal carefully on its side.
- 3. Find the pump and LED light and unravel the cords.
- 4. Feed the LED light cord through the center of the shell and then through the center of the
- pedestal by leaning the pedestal on it's side. Leave 6" of cord slack inside the shell. 5. Feed the pump cord through the center of the shell and then through the center of the pedestal
- by leaning the pedestal on it's side. As you stand the pedestal back upright, pull both cords through the pedestal groove located at the bottom of the pedestal.
- 6. Carefully place the shell on the pedestal. Place a level over the shell. If not leveled, use a shim.
- 7. Find the 2 Hole Rubber Stopper and insert the cords by spreading the slits open. The LED light cord goes through smaller slit and the the pump cord goes through the larger slit.
- 8. Push the 2 Hole Rubber Stopper into the shell's PVC pipe until it is flush.
- 9. Find the tubing and attach by slipping it on to the pump fitting.
- 10. Find the finial and slide it over the tubing until the tubing is sticking out of the top of the finial. Place the finial carefully on the shell.
- 11. Mark the tubing where it is even with the top of the finial. Trim the the tubing a 1/2" shorter from your mark.
- 12. Remove the finial and insert the LED light on the end of the tubing that you just cut.
- 13. Slide the finial back onto the tubing and carefully place it on top of the shell.
- 14. Fill the shell with water. Stop filing when water is visible.
- 15. Attach the transformer to the end of the LED light cord. Plug in the LED light and pump to your GFCI outlet. Your fountain will start running.
- 16.You may need to adjust the water flow. To do so, tilt or lift the finial enough to be able to reach the pump's control dial.