



**MASSARELLI'S**  
MAKERS OF FINE STONE GARDEN ACCENTS

## 3884 - Fleur De Lis Tiered Wall Fountain



### Fountain Information

- Two people are recommended for the installation of this fountain.

### Fountain Components

- 8838B - Three Tiered Base
- 3420S - Bottom Shell
- 3420PL - Bottom Shell Cover Plate
- 3421S - Middle Shell
- 3422S - Top Shell

### Pump Kit 99105 Includes

- 40160 - 160 GPH Pump
- 9958 - 1/2" Kink Free Tubing - 8" Piece
- 9961 - 1/2" Clear Tubing - 4" Piece
- 9940 - Rubber Stopper
- Hose Clamp

### Tools Required

- Screw Driver
- Bubble Level
- Marker or Pen
- Tubing Cutter or Scissors
- Shims (only if leveling is required)

## Set Up Instructions

1. Find the three tiered base and place it on a firm and level area where the fountain will be installed.
2. Find the bottom shell and position it in front of the three tiered base.
3. Find the pump and place it inside the bottom shell. Run the pump's electrical cord through the PVC pipe located inside the bottom shell and then through the PVC pipe located at the bottom of the three tiered base.
4. Find the 8" piece of 1/2" kink free tubing and slide it onto the copper pipe located on the back of the bottom shell. Find one hose clamp and slide it onto the tubing and tighten with a screw driver.
5. Carefully lift the shell and place it half way onto the bottom of the three tiered base.
6. Find the second hose clamp and slip it onto the open end of the 1/2" kink free tubing. Then attach the 1/2" kink free tubing to the copper pipe located at the bottom of the three tiered base. Tighten the hose clamp with a screw driver.
7. Pull the pump's electrical cord until there is no slack left. The pump's electrical cord should be taut. If the pump's electrical cord is not taut once the bottom shell is pushed into place - it will be difficult to retrieve.
8. Carefully shimmy the bottom shell until it is up against the three tiered base.
9. Find the 4" piece of 1/2" clear tubing and attach it to the outlet side of the pump. Then attach the 1/2" clear tubing to the copper pipe located inside the bottom shell.
10. Find the rubber stopper and insert onto the pump's electrical cord by spreading the slit open. The smaller end of the rubber stopper should be facing away from the pump. Insert the rubber stopper snugly into the PVC pipe located inside the bottom shell until it is flush.
11. Find the bottom shell cover plate and place it on top of the opening of the bottom shell. The purpose of the cover plate is to hide the pump.
12. Find the middle shell and place it on the middle tier of the three tiered base.
13. Find the top shell and place it on the top tier of the three tiered base.
14. Fill each shell with water.
15. Plug in the pump to your GFCI outlet. Your fountain will start running.
16. You may need to adjust the water flow. To do so use the flow control dial located on the front of the pump.