



MASSARELLI'S®
MAKERS OF FINE STONE GARDEN ACCENTS

3992 - Fountainette - Sailboat



Fountain Information

- This fountain holds approximately 1 gallon of water.
- Two people are recommended for the installation of this fountain.
- A small fountain cover can be purchased separately for winterization.

Fountain Components

- #8256P - Pedestal
- #3004S - Shell
- #4892 - Sailboat Finial

Pump Kit 99011 Includes

- 1 - 40075 - 75 GPH Pump
- 1 - 9917 - White LED Light
- 1 - 9961 - 8" Piece of 1/2" Clear Tubing
- 1 - 9945 - 2 Hole Rubber Stopper

Tools Required

- Bubble Level
- Marker or Pen
- Tubing Cutter or Scissors

Set Up Instructions

1. Place the pedestal on a firm and level area where the Fountainette will be installed.
2. Find the shell and place beside the pedestal carefully on its side.
3. Find the pump and LED light and unravel the cords.
4. Feed the LED light cord through the center of the shell and then through the center of the pedestal by leaning the pedestal on it's side. Leave 12" of cord slack inside the shell.
5. Feed the pump cord through the center of the shell and then through the center of the pedestal by leaning the pedestal on it's side. As you stand the pedestal back upright, pull both cords through the pedestal groove.
6. Carefully place the shell on the pedestal.
7. Find the 2 Hole Rubber Stopper and insert the cords by spreading the slits open. The LED light cord goes through smaller slit and the the pump cord goes through the larger slit.
8. Push the 2 Hole Rubber Stopper into the shell's PVC pipe until it is flush.
9. Find the tubing and attach by slipping it on to the pump fitting.
10. Find the finial and slide it over the tubing until the tubing is sticking out of the top of the finial. Place the finial carefully on the shell.
11. Mark the tubing where it is even with the top of the finial. Trim the the tubing a 1/2" shorter from your mark.
12. Remove the finial and insert the LED light on the end of the tubing that you just cut.
13. Slide the finial back onto the tubing and carefully place it on top of the shell.
14. Fill the shell with water. Stop filling when water is visible.
15. Plug in the LED light and pump to your GFCI outlet. Your Fountainette will start running.
16. You may need to adjust the water flow. To do so, tilt or lift the finial enough to be able to reach the pump's control dial.