

## SET UP INSTRUCTIONS 3389 STANDING CHERUB WITH FROGS FOUNTAIN

- 1. You will need help to set up this fountain. Level pool on a firm surface where fountain will remain.
- 2. Open the bag containing the pump kit **P29008**. In the kit you will find:
  - 1 KING 400 (400 gallon per hour pump)
  - 1 72" long piece of 1/2" clear tubing
  - 1 8" long piece of 1/2" kink free tubing
  - 2 1" long piece of 3/8" clear tubing
  - 2 1/2" plastic tee
  - 1 1/2" plastic ell
- 3. Find piece of 1/2" clear tubing that is 72" long and cut one piece of this tubing 33" long. Slip the piece of 1/2" clear tubing 33" long thru the two water inlet holes in the pump house. Connect each end to the copper pipes located in each lower corner of the pool. Reach inside pump house and cut the 1/2" clear tubing in the center of the pump house.
- 4. Find the 1/2" plastic tee. With the center connection of the 1/2" plastic tee facing up connect each side of the 1/2" plastic tee to the 1/2" clear tubing inside the pump house. From the remaining 1/2" clear tubing cut two pieces 2" long and one piece 6" long. Take the piece of 1/2" clear tubing 6" long and connect one end to the center connection of the 1/2" plastic tee located inside the pump house. Find the 1/2" plastic ell and connect it to the opposite end of the 1/2" clear tubing 6" long.
- 5. Find the pump and Attach the piece of 1/2" clear tubing 2" long to the outlet side of pump. Find the second 1/2" plastic tee and connect one end to the opposite end of the 1/2" clear tubing 2" long. Find the second piece of 1/2" clear tubing 2" long and connect one end to the center connection of the 1/2" plastic tee already connected to the pump.
- 6. Place the pump into the pump house. Run the power cord of the pump in the groove located in the back of the pool. Connect the end of the 1/2" clear tubing 2" long to the 1/2" plastic ell. Find the piece of 1/2" kink free tubing 8" long and attach it to the end connection of the 1/2" plastic tee located in the pump house.
- 7. Find the large spacer. Holding the large spacer above the pump house run the 1/2" kink free tubing up thru the hole. Center the large spacer on the pump house and flush with back of the pool. Shim if necessary. Find the standing cherub with shell statue. On a padded surface lay statue on its back to expose the copper tubing located in the bottom of statue. Clean any tape or excess concrete from copper tubing.
- 8. Place the standing cherub with shell onto the large spacer. Tilt the standing cherub with shell statue enough to connect the piece of 1/2" kink free tubing to the copper tubing on the bottom of statue. Push the extra 1/2" kink free tubing back down the hole of the large spacer as you position the statue on the large spacer.
- 9. Find the two frog on leaves and the two pieces of 3/8" clear tubing 1" long. Clean any tape or excess concrete from the copper tubing located on the bottom of each frog. Slip the 3/8" clear tubing 1" long onto this copper tubing. From the remaining 1/2" clear tubing cut two pieces about 5" long and slip one end of the 1/2" clear tubing 5" long onto the connection on bottom of each frog. Connect each frog onto the copper tubing located in each corner of the pool. Cut 1/2" clear tubing so that each frog will sit properly on pool.
- 10. Fill pool with about 6" of tap water and plug pump into a 110VAC GFCI protected outlet. **3389sup 4/24/07**