



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3458 53" DOLPHIN FOUNTAIN

Open bag containing the pump kit **P13006**. In the kit you will find:

- | | |
|---|----------------------|
| 1 – 40160 (160 gallons per hour pump) | 2 - 3/8" plastic tee |
| 1 - 2" long piece of 1/2" clear tubing | 1 - rubber stopper |
| 1 - 1" long piece of 3/8" clear tubing | 1 - hose clamp |
| 1 - 22" long piece of 3/8" kink free tubing | 1 - metal restrictor |

1. Place pedestal on a firm level surface where fountain will remain. Place the shell on the pedestal with the water intake hole towards the rear.

2. Find the piece of 3/8" kink free tubing 22" long and cut one piece 8" long, two pieces 5" long and one piece 3" long. Find the piece of 3/8" clear tubing 1" long. Find a 3/8" plastic tee. On the middle connection of the 3/8" plastic tee attach the piece of 3/8" clear tubing 1" long. Find the piece of 1/2" clear tubing 2" long and attach it over top of the 3/8" clear tubing 1" long. On an end connection of the 3/8" plastic tee attach the piece of 3/8" kink free tubing 8" long and slip on the metal restrictor about midway on the 3/8" kink free tubing 8" long. **Tighten the restrictor onto the 3/8" kink free tubing and then loosen restrictor four half turns.** On the opposite end connection of the 3/8" plastic tee attach the piece of 3/8" kink free tubing 3" long. Find the second 3/8" plastic tee and attach an end connection to the opposite end of the 3/8" kink free tubing 3" long. On the opposite end and middle connections of the second 3/8" plastic tee attach the two pieces of 3/8" kink free tubing 5" long.

3. Find the pump. On the rear side of the pump there is a slide type flow control. Adjust the built in flow control slide on the pump to the full open position (+). Place pump into the pump house located in center of the shell and run the plug end of the electrical cord down the PVC pipe located in the pump house and down thru the pedestal. Retrieve cord from under pedestal and place in groove in bottom of pedestal. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust position of the rubber stopper on the power cord if necessary.

4. Position the shell on pedestal and level. To level shell, place level on top rim of the pump house in the center of shell. Level in (2) Two directions left to right and front to back. **Shim as needed.**

5. Find the triple dolphins statue. On a padded surface carefully lay the triple dolphins on its side. On the bottom you will see three copper pipes. Remove any excess concrete or tape from both ends of the copper pipes. **Find the tubing assembly and attach the 3/8" kink free tubing 8" long to the copper pipe connected to the LOWEST dolphin. Attach the 3/8" kink free tubing 5" long (END CONNECTION of the 3/8" plastic tee) to the copper pipe connected to the HIGHEST dolphin. Attach the 3/8" kink free tubing 5" long (MIDDLE CONNECTION of the 3/8" plastic tee) to the copper pipe connected to the MIDDLE dolphin. Carefully lift the triple dolphins with the tubing attached and connect the 1/2" clear tubing 2" long to the pump.**

6. Fill shell with water and plug pump into a 110VAC GFCI protected outlet. To adjust the flow of water to all three dolphins lift the triple dolphins statue enough to have someone adjust the water flow using the metal restrictor until the desired result is achieved.

3458sup 11/7/07