



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3464 – CANDIA SQUARE FOUNTAIN

Open the bag containing the pump kit **P46016**. In the kit you will find:

1 - 40460 (460 gallon per hour pump)	1 – 1" x 3/4" reducing female adaptor	1 – rubber stopper
1 – 3/4" kink free tubing 16" long	1 – 3/4" barb adaptor	1 – tube of silicone
1 – 1" PVC pipe 3" long		

1. Find the fountain base, the pump and the rubber stopper. Slip the rubber stopper onto the power cord about 12" from the body of the pump with the smaller end facing away from the pump.
2. Run the plug end on power cord of the pump down the PVC insert located in the center of the fountain base and out the bottom of the fountain base. Retrieve the power cord from under the fountain base and place in the groove in the bottom of the fountain base.
3. Find the tube of silicone. **For a watertight seal apply silicone around the top inside edge of the PVC insert and around the outside edge of the rubber stopper. Insert the rubber stopper snugly into the PVC insert. Apply more silicone around the top of the rubber stopper and the wire. Do not skimp on the silicone you want a watertight seal.**
4. Place the fountain base on a firm and level area where the fountain will remain.
5. Find the 1" x 3/4" reducing female adaptor, the 3/4" barb adaptor and screw the two pieces together. Find the 3/4" kink free tubing and attach one end to the barbed end of the 3/4" barb adaptor. Find the piece of 1" PVC pipe 3" long and using PVC glue insert one end into the slip end of the 1" x 3/4" reducing female adaptor until it bottoms out.
6. Find the top shell and **CAREFULLY** place it on a padded surface with the bottom side up. In the bottom of the top shell there is a 1" PVC coupling. Clean any tape and or dirt from the PVC coupling. Insert the opposite end of the 1" PVC pipe 3" long into the 1" PVC coupling located in the bottom of the top shell until it bottoms out.
7. Find the pump house and position it over the pump and centered within the scribe lines in the bottom of the fountain base. **CAREFULLY** place the top shell on the pump house while feeding the tubing down the hole in the top of the pump house. Position the top shell on the pump house.
8. Reach in the square pump house opening and attach the end of the 3/4" kink free tubing to the outlet side of the pump. Position the pump on its side inside the pump house.
9. Find the pump house plug and position it in the square pump house opening. Find the finial and position it over the hole in the center of the top shell.
10. Find the drain plug and insert the snugly into the drain insert located in the fountain base. Remove any tape and or dirt from the drain insert before you insert the drain plug.
11. Fill the fountain base with tap water. Plug the pump into a 110VAC GFCI protected outlet. If necessary, adjust the water flow using the dial type flow control located on the front of the pump.

3464sup

5/15/15