



# MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

## SET UP INSTRUCTIONS

### 3875 79" THREE TIER CORTONA WITH PINEAPPLE FOUNTAIN

Open bag containing the pump kit **P40008**. In the kit you will find:

- |   |                    |
|---|--------------------|
| 1 - 40400 (400 gallon per hour pump)    | 1 - rubber stopper |
| 1 - 48" long piece of 3/4" clear tubing |                    |
| 1 - 5" long piece of 1" clear tubing    |                    |

1. Place the pedestal on a firm and level surface where fountain will remain. To level pedestal, place level on the top of the pedestal. Level in (2) Two directions left to right and front to back. Shim as needed. Place the largest shell on the ground near the pedestal.
2. Find the pump and the rubber stopper. Place pump in the pumphouse in the center of the largest shell and run the plug end of the power cord down the PVC pipe located in the pumphouse. Retrieve the power cord from under shell. Run the power cord down the hole that is through the pedestal. Retrieve the power cord from under pedestal and place in groove in bottom of pedestal. Place the largest shell on the pedestal. While placing the shell on the pedestal carefully pull the remainder of the power cord until all is hidden inside the fountain. Slip the rubber stopper onto the power cord about 15" from the pump. Insert the rubber stopper snugly into the PVC pipe.
3. Position the largest shell on pedestal and level. To level shell, place level on the top rim of the pump house in the center of shell. Level in (2) Two directions left to right and front to back. Shim as needed.
4. Find the second shell. Position the shell on top of pumphouse in center of shell and level as stated in step #3. Find the piece of 3/4" clear tubing 48" long. Run one end of the 3/4" clear tubing down the hole that is in the center of the second shell down into the large shell. Reach into the opening in the pumphouse and connect the 3/4" clear tubing to the outlet of the pump.
5. Find the third shell and run the 3/4" clear tubing up thru the hole in the center housing of the shell. Position the third shell on top of the second shell and level. To level shell, place level on the center housing of the shell. Level as stated in step #3.
6. Cut the 3/4" clear tubing 8 1/2" above the top surface of the center housing on the third shell. Find the finial. In the center of the finial you will see a PVC pipe. Insert the 3/4" clear tubing into the PVC pipe in the bottom of the finial and slide the finial down onto the center housing of the second shell. Position the finial on the fountain.
7. Find the drain plugs and insert snugly into the drain inserts located in the two shells of the fountain. Remove any tape and or dirt from the drain insert before you insert the drain plug.
8. Fill shells with tap water and plug pump into a 110VAC GFCI protected outlet. Adjust the water flow to the finial using the dial type flow control located on the front of the pump until the desired result is achieved.

3688sup 4/14/10