

SET UP INSTRUCTIONS 3982 - FOUNTAINETTE - LIGHTHOUSE

Open the bag containing the pump kit **P13019**. In the kit you will find:

0	o i i
1 - 40160 (160) gallon per hour pump)
1 –1/2" clear tubing 13" long	

1 – 2-hole rubber stopper 1 - LED light kit (WHITE)

1 - hose clamp

1. Place the fountain pedestal on a firm and level area where the fountain will remain. On a padded surface place the fountain bowl along side the pedestal. Inside the fountain bowl there is a PVC pipe. Find the pump and the LED light kit. Run the plug end of both power cords down the PVC pipe and out the bottom of the bowl leaving about 12" of wire from the pump and 18" of wire from the LED light inside the bowl.

2. Run both power cords down the hole located in the pedestal and out the bottom. Retrieve both power cords from under pedestal and place both power cords in the groove in the bottom of the pedestal. Carefully place the fountain bowl on the pedestal. Pull the remainder of both power cords out from the bottom of the pedestal. Position the bowl on the pedestal.

3. Find the 2-hole rubber stopper. Slip the 2-hole rubber stopper onto the power cord of the pump and the power cord of the LED light. Position the 2-hole rubber stopper about 12" from the body of the pump and about 14" from the LED light. Insert the 2-hole rubber stopper snugly into the PVC pipe.

4. On the front of the pump there is a dial type flow control. Set the dial to the 5 o'clock position.

5. Find the 1/2" clear tubing 13" long and the hose clamp. Attach the 1/2" clear tubing to the outlet side of the pump with the hose clamp. Insert the LED light head into the opposite end of the 1/2" clear tubing. Place the pump in the center of the bowl with the tubing assembly facing up. Add 6" of water in the fountain bowl.

6. Find the lighthouse finial and place it onto the bowl **CAREFULLY** guiding the LED light up through the hole in the center of the lighthouse. Position the lighthouse final centered inside of the bowl. If necessary, trim the 1/2" clear tubing shorter.

7. On the top of the lighthouse finial there are three flat surfaces that are for the round lighthouse top. Place a dab of silicone on each of the three flat surfaces and then position the round lighthouse top on the lighthouse finial. Let dry.

8. Connect the power cord on the LED light to the transformer. Plug both the pump and the LED light transformer into a 110VAC GFCI protected outlet.

3982sup 4/3/13