

## SET UP INSTRUCTIONS 3458 53" DOLPHIN FOUNTAIN 3525 46" DOLPHIN FOUNTAIN

Open bag containing the pump kit **P13006**. In the kit you will find:

1 – 40160 (160 gallons per hour pump)
2 - 3/8" plastic tee
1 - 2" long piece of 1/2" clear tubing
1 - 1" long piece of 3/8" clear tubing
1 - 22" long piece of 3/8" kink free tubing
1 - metal restrictor

- 1. Place pedestal on a firm level surface where fountain will remain. Place the shell centered on the pedestal.
- 2. Find the piece of 3/8" kink free tubing 22" long and cut one piece 8" long, two pieces 5" long and one piece 3" long. Find the piece of 3/8" clear tubing 1" long. Find a 3/8" plastic tee. On the middle connection of the 3/8" plastic tee attach the piece of 3/8" clear tubing 1" long. Find the piece of 1/2" clear tubing 2" long and attach it over top of the 3/8" clear tubing 1" long. On an end connection of the 3/8" plastic tee attach the piece of 3/8" kink free tubing 8" long and slip on the metal restrictor about midway on the 3/8" kink free tubing 8" long. **Tighten the restrictor onto the 3/8" kink free tubing and then loosen restrictor four half turns.** On the opposite end connection of the 3/8" plastic tee attach the piece of 3/8" kink free tubing 3" long. Find the second 3/8" plastic tee and attach an end connection to the opposite end of the 3/8" kink free tubing 3" long. On the opposite end and middle connections of the second 3/8" plastic tee attach the two pieces of 3/8" kink free tubing 5" long.
- 3. Find the pump. Place pump into the pump house located in center of the shell and run the plug end of the power cord down the PVC pipe located in the center of the pump house and down thru the pedestal. Retrieve power cord from under pedestal and place in groove in bottom of pedestal. Slip the rubber stopper onto the power cord about 6" from the body of the pump with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust position of the rubber stopper on the power cord if necessary.
- 4. Position the shell on pedestal and level. To level shell, place level on top rim of the pump house in the center of shell. Level in all directions. **Shim as needed**.
- 5. Find the triple dolphins statue. On a padded surface carefully lay the triple dolphins on its side. On the bottom you will see three copper pipes. Remove any excess concrete or tape from both ends of the copper pipes. Find the tubing assembly and attach the 3/8" kink free tubing 8" long to the copper pipe connected to the LOWEST dolphin. Attach the 3/8" kink free tubing 5" long (END CONNECTION of the 3/8" plastic tee) to the copper pipe connected to the HIGHEST dolphin. Attach the 3/8" kink free tubing 5" long (MIDDLE CONNECTION of the 3/8" plastic tee) to the copper pipe connected to the MIDDLE dolphin. Carefully lift the triple dolphins with the tubing attached and connect the 1/2" clear tubing 2" long to the outlet of the pump. Position the dolphin statue on the pump house
- 6. Fill shell with tap water and plug pump into a 110VAC GFCI protected outlet. To adjust the flow of water to the triple dolphins reach in the pump house opening and locate the metal restrictor. Adjust the metal restrictor plus or minus along with the dial type flow control located on the front of the pump until the desired result is achieved.

3458sup 12/13/17

3525sup 1/15/18