

## SET UP INSTRUCTIONS 3699 - 34" TRANQUILLITY SPILL FOUNTAIN WITH BIRDS

Open the bag containing the pump kit **P16026**. In the kit you will find:

1 - 40160 (160 gallon per hour pump)

1 - LED light kit (WHITE)

1 - hose clamp

1 –1/2" kink free tubing 12" long

1 – butyl tape 2" long

1 - tube of silicone

1 – 2-hole rubber stopper

- 1. Place the pedestal on a firm and level area where the fountain will remain. Place the large bowl on the pedestal.
- 2. Located inside the large bowl there is a PVC insert. Remove any tape and or dirt from inside the PVC insert before you insert the rubber stopper. Find the pump and the LED light and run the plug end on both power cords down the PVC insert located in the center of the large bowl and down the hole in the pedestal. Leave about 12" of slack on both power cords inside the large bowl.
- 3. Find the 2-hole rubber stopper and the tube of silicone. Apply a dab of silicone in both holes in the rubber stopper. Slip the rubber stopper onto the power cords about 6" from the body of the pump and about 12" from the LED light head with the smaller end of the rubber stopper facing away from the pump and the LED light. Apply silicone around the inside edge of the PVC insert located in the large bowl and around the outside edge of the rubber stopper. Retrieve both power cords from under the pedestal and place both in the groove in the bottom of the pedestal. Insert the rubber stopper snugly into the PVC insert. Apply more silicone on top and around the rubber stopper and the power cords. **Don't skimp on the silicone you want a watertight seal.**
- 4. Find the piece of 1/2" kink free tubing 12" long and the hose clamp. Attach one end of the 1/2" kink free tubing to the outlet of the pump with the hose clamp. Attach the opposite end of the 1/2" kink free tubing to the 1/2" barb fitting on the LED light.
- 5. Position the large bowl on the pedestal and level in all directions. Shim if needed.
- 6. Find the drain plug and insert it snugly into the drain insert located in the large bowl. Remove any tape and or dirt from the drain insert before you insert the drain plug.
- 7. Position the pump in the pump house that is located in the large bowl.
- 8. Find the top bowl and Carefully place the top bowl onto the pump house located in the center of the large bowl while Carefully guiding the LED light head up through the hole in the center of the top bowl.
- 9. Position the top bowl on the pump house and level in all directions. Shim if needed.
- 10. Find the butyl tape. Roll the butyl tape back and forth between the palms of your hands until it is a round strip about 1/4" diameter and 5" long. Apply the strip of butyl tape around the LED light head. Push the LED light head down into hole in the center of the top bowl and seal the hole around the LED light head with the butyl tape strip.
- 11. Position the bird finial around the center housing of the top bowl.
- 12. Fill both bowls with tap water. Connect the power cord on the LED light to the transformer. Plug the power cord of the pump and the LED light transformer into a 110VAC GFCI protected outlet. Adjust the water flow to the top bowl using the dial type flow control located on the front of the pump until the desired result is achieved.

3699sup 6/15/20